



| | | | | | , |
|----------|--------------|-------------------------|------|--------------|-------------------|
| ITEM NO. | PART NUMBER | DESCRIPTION | QTY. | MATERIAL | ULTIMATE STRENGTH |
| 1 | ASH-66-BC | ANCHOR SHACKLE | 1 | FORGED STEEL | 60,000 LBS. |
| 2 | SYCR-87 | SOCKET Y-CLEVIS | 1 | DUCTILE IRON | 50,000 LBS. |
| 3 | Y2TT050D1800 | YOKE | 1 | DUCTILE IRON | 50,000 LBS. |
| 4 | - | CORONA FREE SUSP. CLAMP | - | ALUMINUM | 25,000 LBS. |
| 5 | - | Y-CLEVIS INSULATOR | - | COMPOSITE | - |

NOTE: INSULATORS AND CONDUCTOR KIT SOLD SEPARATELY

ASSEMBLY CAT. NO. X3SS1YB50A2

This drawing contains confidential information that is the property of MacLean Power, L.L.C. ("MacLean"). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to "MacLean Power, L.L.C., 11411 Addison Street, Franklin Park, Illinois 60131, USA."

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN: **INCHES** TOLERANCES ARE: X +/- 0.1 .XX +/- 0.03 +/- 0.015 .XXX +/- 1.0 ANGLES



DRAWING NUMBER: DO NOT SCALE DRAWING X3SS1YB50A2 SHEET NAME:

SINGLE STRING **ASSEMBLY**

CAD GENERATED DRAWING DO NOT MANUALLY UPDATE DESIGN DATE: 3/25/24 DRAWN BY: JIP ENGINEER: APPROVED: